

■ PERFORMANCE AND SPECIFICATION

1. Performance

Heater	Heater Output	W (Kcal/h)	5200 (4477)
	Air Flow Volume	m ³ /h	350
	Power Consumption	W	Less than 200
Air Conditioning	Cooling Capacity	W (Kcal/h)	5600 (4815)
	Air Flow Volume	m ³ /h	550
	Power Consumption	W	Less than 250

2. Specification

Ventilation and Heater Core	Heater Core	Type	SFA (Straight Flow Aluminum)-II
		Size W x H x L mm (in.)	263.9 x 100 x 27 (10.4 x 3.9 x 1.1)
		Fin Pitch mm (in.)	1.8 (0.07)
	Blower	Fan Type	Semi Sirocco
		Fan Size Dia. x H mm (in.)	165 x 70 (6.5 x 2.8)
Air Conditioning	Condenser	Type	MF (Multi-flow)
		Size W x H x L mm (in.)	646 x 255 x 22 (25.4 x 10.0 x 0.9)
		Fin Pitch mm (in.)	2.7 (0.11)
	Evaporator	Type	RS (Revolutionary super-slim Structure)
		Size W x H x L mm (in.)	293.1 x 211 x 38 (11.5 x 8.3 x 1.5)
		Fin Pitch mm (in.)	3.0 (0.12)
	Compressor	Type	ES27 (Electric Inverter Type)
		Oil Type	ND11
	Refrigerant	Type	HFC 134a
		Charge Volume g	450 to 550